Original Research Paper

Experimental investigation of the combustion characteristics of Mahua oil biodiesel-diesel blend using a DI diesel engine modified with EGR and nozzle hole orifice diameter

M. Vijay Kumar^{1,*}, A. Veeresh Babu², P. Ravi Kumar², S. Sudhakara Reddy¹

¹Department of mechanical engineering, Malla Reddy Engineering College, Hyderabad, Telangana, 500100, India.

²Department of mechanical engineering, National Institute of Technology Warangal, Warangal, Telangana, 506004, India.

HIGHLIGHTS

- Engine modification through reducing NHD improved combustion characteristics but deteriorated NO_x emissions.
- Application of partially-cooled EGR could compensate for the adverse impacts of engine modification on NO_x emissions.
- The EGR rate of 10% was found promising in substantially reducing NO_x emissions at all loads.
- High EGR rates esp. at higher loads, adversely affected the performance and emission characteristics of the modified.

GRAPHICAL ABSTRACT

ARTICLE INFO

Article history:

Received 12 June 2018

Received in revised form 10 August 2018

Accepted 12 August 2018

Available online 1 September 2018

Keywords:

Diesel engine modification
Injector nozzle hole diameter
Biodiesel
Combustion characteristics
EGR
NO_x reduction

ABSTRACT

Engine modification through reducing nozzle hole diameter (NHD) (i.e., from the base value of 0.28 to the modified value of 0.20 mm) has been shown as an effective strategy in improving engine performance, combustion, and emission parameters. However, it has also led to substantial increases in NO_x emission as a major shortcoming. In light of that, the present study was aimed at overcoming this challenge through the application of a partially-cooled exhaust gas recirculation (EGR) system. More specifically, Mahua oil biodiesel-diesel blend (B20) and neat diesel were tested on a modified single cylinder diesel engine under five different engine loads (i.e., 2.46, 4.92, 7.38, 9.84, and 12.3 kg) and in the presence of varying EGR rates (i.e., 10, 20, and 30%). The results obtained revealed that the performance, combustion, and emission characteristics of the modified engine (3-hole nozzle with an orifice diameter of 0.20 mm) were improved for both neat diesel and B20 except in the case of NO_x, in comparison with those of the conventional diesel engine (3-hole nozzle with an orifice diameter of 0.28 mm). The considerable increases in NO_x emissions caused by the smaller orifice NHD could be successfully compensated for through the implementation of the partially-cooled EGR. Overall and based on the findings of the present study, the proposed engine modification in the presence of partially-cooled EGR rate of 10% could be recommended as efficient combustion conditions for 20% blend of Mahua oil biodiesel and diesel. However, further increments in the EGR rate and in particular at higher loads, adversely affected the performance and emission characteristics of the modified engine due to the recirculation of high amounts of unburnt soot, CO₂, H₂O, as well as of O₂ deficiency.

© 2018 BRTeam. All rights reserved.

* Corresponding author at: Tel.: +91 9701339886

E-mail address: vijaykumar.iitm37@gmail.com

Abbreviations

BP	Brake Power
BSFC	Brake Specific Fuel Consumption
BTE	Brake Thermal Efficiency
bTDC	before Top Dead Center
CI	Compression Ignition
CO	Carbon Monoxide
CO ₂	Carbon Dioxide
CR	Compression Ratio
EGR	Exhaust Gas Recirculation
DI	Direct Injection
HC	Hydrocarbon
HRR	Heat Release Rate
ID	Ignition Delay
IP	Ignition Pressure
IT	Injection Timing
NHD	Nozzle Hole Diameter
NO _x	Oxides of Nitrogen
PM	Particulate Matter
SOC	Start of Combustion
SCR	Selective Catalytic Reduction

1. Introduction

Growing interests in achieving higher power with better fuel economy at a lesser maintenance cost have been the driving force behind the increasing number of compression ignition (CI) engine vehicles. In line with that, engine manufacturers constantly strive to further develop the CI engine technology to more efficiently meet the above-mentioned objectives. It should be mentioned that among these objectives, reducing exhaust gas emissions in order to meet the increasingly stringent emissions standards/policies is of utmost importance. Therefore, different engine modifications, methods/approaches for exhaust gas after-treatment, and strategies leading to more optimized combustion such as the application of more environmentally-friendly fuels/fuel additives have attracted a great deal of attention (Hussain et al., 2012; Vijay Kumar et al., 2018a). A number of these solutions are discussed herein.

1.1. Biodiesel

Biodiesel is defined as the mono-alkyl esters of long chain fatty acids resulting from vegetable oils or animal fats (Venkanna and Reddy, 2009; Vijay Kumar et al., 2017a). The critical properties of biodiesel, such as being non-toxic, high cetane number, oxygen content, absence of sulfur, high inherent lubricity, and being biodegradable, make this alternative fuel an ideal replacement for mineral diesel. Biodiesel can be used in neat form or with diesel at different blending ratios with no or little engine modification. Nevertheless, engine manufacturers recommend biodiesel blending ratios of up to 20% for the existing diesel engines (Mo et al., 2016).

In spite of the above-mentioned advantages, biodiesel is associated with a number of disadvantages as well including lower volumetric energy capacity, lower oxidative stability, inferior cold flow properties, higher kinematic viscosity, and higher NO_x emissions (Can et al., 2016). Moreover, the widespread use of edible vegetable oil for biodiesel production has sparked much concern over the growing food vs. fuel competition over food resources/water/land. Additionally, edible oils could be more costly to use as biodiesel feedstock jeopardizing the economic viability of the biodiesel production process. Hence, the application of non-edible oil crops such as *Sterculia foetida*, Soapnut, Jatropha, Mahua, Pongamia, Polanga, Neem, etc. has been offered to overcome these challenges (Sahoo et al., 2007; Kumar and Sharma, 2011). Table 1 tabulates the estimated oil yields of mahor non-edible oil crops used as biodiesel feedstock.

While the application of many of the non-edible oil crops as biodiesel feedstock is still being assessed, these crops in general offer the following advantages (Atabani et al., 2013):

- The cultivation of non-edible oil feedstock requires non-agricultural and marginal land with little fertilizer and irrigation requirements.

- Non-edible oil crops can also be grown in semi-arid zones with an annual precipitation of around 200 mm.
- Following oil extraction, the seed cakes can be used as fertilizer for soil improvement and/or biopesticide (Vijay Kumar et al., 2018b).

Table 1.

Estimated oil yields of non-edible oil crops used for biodiesel production.

Type of oil	Oil yield (T/ha)	Oil yield per seed (wt. %)	References
Mahua	3.6 00	44.43 - 61.5	Jena et al. (2010); Kumar and Sharma (2011); Soo-Young (2011)
Polanga	4.680	50	Azam et al. (2005); Sahoo et al. (2006)
Jatropha	1.900 – 2.250	35 - 40	Achten et al. (2008); Gui et al. (2008); Pinzi et al. (2009); Singh and Singh (2010); Koh and Ghazi (2011); Silitonga et al. (2011)
Neem	2.670	20 - 30	Azam et al. (2005); Nabi et al. (2006); Kumar and Sharma (2011); Sharma et al. (2011); Soo-Young (2011)
Pongamia	0.225 - 2.250	30 - 40	Azam et al. (2005); Karmee and Chadha (2005); Gui et al. (2008); Naik et al. (2008); Pinzi et al. (2009); Singh and Singh (2010); Soo-Young (2011)
Rubber seed	0.040 - 0.120	40 - 50	Ramadan and Morsel (2003); Ramadhas et al. (2005a); Ramadhas et al. (2005b); Kumar and Sharma (2011); Soo-Young (2011)
Castor	1.188	45 - 50	Koutroubas et al. (1999); Saka (2005); Soo-Young (2011)

1.2. Biodiesel application without engine modifications

Many research studies have recommended the application of biodiesels produced from different oil feedstock without requiring any engine modifications. For instance, Polanga oil methyl ester (POME) and its blends were combusted at varying loads by Sahoo et al. (2007). The authors claimed more favorable engine performance parameters such as brake thermal efficiency (BTE) and brake specific energy consumption (BSEC) using POME blends compared with neat diesel. They also argued that smoke opacity and hydrocarbon (HC) emissions were decreased in response to POME inclusion while NO_x was increased owing to the oxygen content of biodiesel (Sahoo et al., 2007). Similar results were reported by Mofijur et al. (2013) who investigated two blending ration of biodiesel into diesel, i.e., B10 and B20. They indicated that the average BSFC values obtained for B10 (278.46 g/kWh) and B20 (281.9 g/kWh) were higher than that of neat diesel (273.5 g/kWh).

Whereas, compared to neat diesel, B10 and B20 led to lower CO (16% and 25%, respectively) and HC (3.84% and 10.25%, respectively) emissions, but a slightly higher NO_x emissions (3% and 6%, respectively (Mofijur et al., 2013). In a different study, Karanja biodiesel and its blends were found compatible with the existing diesel engines (Chauhan et al., 2013). From the unfavorable combustion characteristics point of view, it was found that compared with neat diesel, Karanja biodiesel blends led to 3-5% less BTE, lower in-cylinder pressure, and lower heat release rate (HRR), but increased NO_x emissions (Chauhan et al., 2013). Rahman and Phadatare (2004) as well as Agarwal and Dhar (2013) also studied the combustion characteristics of Karanja biodiesel and claimed reductions in emissions, i.e., CO, HC, and smoke.

These findings were in line with those of the other investigations on biodiesel produced from other oil feedstocks such *Pongamia Pinnata* biodiesel (Sureshkumar et al., 2008), Mahua oil biodiesel (Raheman and Ghadge, 2007; Vijay Kumar et al., 2017b), mango seed oil biodiesel (Vijayaraj and Sathiyagnanam, 2016), palm and Jatropha biodiesel (Rahman et al., 2014), etc. Overall, these studies are unanimous in concluding that biodiesel can be used by up to 20% (i.e., B20) in the existing diesel engines without modifications and that it could lead to reduced emissions (except NO_x).

1.3. Biodiesel application along engine modifications

Some research works have been focused on investigating the effects of various engine modifications, e.g., compression ratio (CR), injection timing (IT), pressure opening, etc. on diesel engines powered by biodiesel-diesel blends. For instance, Ganapathy et al. (2011) claimed reductions in BSFC as well as HC, CO, and smoke emissions by applying variations in injection timing when using *Jatropha* biodiesel. They also argued that HRR, pressure, and BTE could be increased while NO_x emissions could be reduced through such variations. In a different study, Gnanase Karan et al. (2016) studied the combustion characteristics of a diesel engine running on fish oil biodiesel and its blends at different injection timings, i.e., 21° bTDC, 24° bTDC, and 27° bTDC. They reported shorter ignition delays (ID) and lower HRRs for biodiesel blends. They also argued that through the retardation of IT, a number of emission and combustion parameters including NO_x, HC, CO, peak pressure, ID, combustion duration, and HRR were decreased while advancement in IT led to opposite results (Gnanase Karan et al., 2016).

Variations in ignition pressure (IP) has also taken into account by a number of investigations. For instance, Channappattana et al. (2015) and Shehata et al. (2015) studied the effects of varying IPs on the combustion characteristics of Honne biodiesel and corn/soybean biodiesel blends, respectively. These authors concluded increases in NO_x emissions and decreases in HC, CO, and smoke opacity in response to increasing IP. In a recent investigation, Dubey and Gupta (2018) took into consideration the effects of increasing compression ratio (CR) (i.e., 15.5:1, 17:1, 18.5:1, and 20:1) on the performance and emissions profile of a dual biofuel (*Jatropha* biodiesel and turpentine oil). They claimed that at the CR of 20:1, the investigated biofuel led to the most favorable results, i.e., increased BTE by 2.17% as well as decreased CO, HC, NO_x emissions, and smoke opacity by 13.04%, 17.5%, 4.21%, and 30.8%, respectively (Dubey and Gupta, 2018). Lower HC and CO emissions were also recorded by Sivaramakrishnan (2018) through optimizing IP at 200 bar and CR at 18:1 when combusting a 25% blend of *Karanja* biodiesel. Similar results were also reported by Jindal et al. (2010) who claimed that higher CRs and higher IPs improved the engine performance of a diesel engine running on *Jatropha* biodiesel.

1.5. Biodiesel application with after-treatment technologies

Efforts to reduce the NO_x emissions associated with the application of biodiesel have been intensified over the last decade. In line with that, selective catalytic reduction (SCR) and exhaust gas recirculation (EGR) have been offered as proven technologies for reducing NO_x emissions. For instance, in a study, Hussain et al. (2012) investigated the effect of EGR (10%, 15%, 20% and 25%) on a 3-cylinder, constant speed, and air-cooled CI diesel engine and concluded that at lower loads, higher rates of EGR could be applied without negatively affecting the fuel economy and efficiency, while leading to reduced NO_x. Duraisamy et al. (2011) combusted *Jatropha* biodiesel using EGR and argued that EGR of 15% was optimal in terms performance improvement and reduction in NO_x emission. Similar findings verifying the favorable impacts of EGR have also been reported by other studies (Kusaka et al., 2000; Rajan and Senthilkumar, 2009; Bani et al., 2010; Fontana and Galloni, 2010; Mani et al., 2010). These improvements in response to EGR application could be explained by the resultant high intake temperature, which improves flame propagation in the combustion chamber (Sasaki et al., 1998).

In our recently published report, the combination of Mahua oil biodiesel blend (B20) application with engine modification, i.e., the implementation of smaller orifice nozzle hole diameter (NHD), was shown to lead to improved combustion characteristics (Vijay Kumar et al., 2018b). However, the combined strategy also led to NO_x augmentation as its only drawback observed. These outcomes could be ascribed to the more efficient atomization of the fuel particles triggered by the smaller orifice NHD and the consequently more effective fuel combustion taking place in the combustion chamber on one hand and the high oxygen content of the fuel blend on the other hand (Vijay Kumar et al., 2018b). In light of that, the present study was set to overcome the shortcoming of the investigated strategy or in better words, to reduce NO_x emissions by employing EGR while using Mahua oil biodiesel blend and small orifice NHD.

2. Experimental Procedure

2.1. Biodiesel preparation

Biodiesel was produced as described in our previous report (Vijay Kumar et al., 2018b). Briefly, inedible Mahua oil was transesterified through a two-step procedure. This strategy was employed owing to the high free fatty acids (FFA) of this oil feedstock, i.e., 21%. In the first step, the FFA content was reduced through mixing 0.35 v/v of methanol and 1% v/v of concentrated H₂SO₄ with the pre-heated Mahua oil at 60 °C for 1 h. Subsequently, the resultant oil was transesterified by using 0.25 v/v of methanol and 0.7% w/v of KOH at 60 °C for 1 h. Following glycerin decantation, crude biodiesel was washed with 50 °C distilled water three times. Finally, anhydrous CaCl₂ was added to the resultant product, heated gently at 50 °C while shaken vigorously. Dry purified Mahua oil biodiesel was obtained after CaCl₂ separation and blended with diesel to obtain B20 fuel.

Fuel properties of diesel, Mahua oil biodiesel and its 20% blend with diesel (B20) are presented and compared in Table 2. The chemical compositions of diesel and Mahua oil biodiesel are tabulated in Table 3.

Table 2.
Fuel properties of neat diesel, Mahua oil biodiesel as well as its 20% blend with diesel (B20).*

Property	Unit	Diesel	Mahua oil biodiesel	B20
Colour	-	Light brown	Slight brown yellow	Light brown
Density at 35 °C	Kg/m ³	819	867	831
Viscosity at 40 °C	cSt	2.89	4.86	3.36
Calorific value	kJ/kg	44296	38513	43761
Fire point	°C	52	140	ND ¹
Flash point	°C	48	108	ND
Pour point	°C	-5	10.2	ND
Cloud point	°C	-10	14.5	ND
Boiling point	°C	282-338	320	ND
Cetane number	-	49	52	ND

¹ ND = Not determined

* Source: Vijay Kumar et al. (2018b). With permission from Elsevier. Copyright© 2018.

Table 3.
Comparison of chemical composition of diesel and Mahua oil biodiesel.*

Description	Diesel	Mahua oil biodiesel
Carbon (%)	86.5	77.9
Oxygen (%)	0	9.3
Nitrogen (%)	0.18	<0.001
Hydrogen (%)	13.2	12.8

* Source: Vijay Kumar et al. (2018b). With permission from Elsevier. Copyright© 2018.

2.2. Engine modifications with fuel injector nozzle and EGR

First, the injection nozzle system of a diesel engine was modified to smaller orifice diameter in order to improve the performance and to reduce the harmful emissions as reported previously (Vijay Kumar et al., 2018b). Briefly, the reduction of NHD significantly affected the air-fuel mixture formation, atomization, and evaporation leading to improved BTE, BSFC, and HRR and reduced emissions (except NO_x) in the investigated CI engine. Subsequently, to overcome the challenge associated with the NHD modification, the coupling of a partially-cooled EGR system to the diesel engine was investigated.

Parametric details of the fuel injection systems used including the differences between the base and modified nozzle orifice diameters are presented in Table 4. For better understanding, cross-sectional views of the nozzle hole geometries are also shown in Figure 1.

Table 4.
Parametric details of the fuel injection systems used.

S. No.	Nozzle label	No. of holes	Diameter of orifice hole	Standard nozzle opening pressure
1	NHD (base)	3	0.28 mm	210 bar
2	NHD (modified)	3	0.20 mm	210 bar

Fig.1. Cross section views of the nozzles with different orifice diameters. Source: Vijay Kumar et al. (2018b). With permission from Elsevier. Copyright© 2018.

A computerized single cylinder diesel engine was employed to study the effects of reduced nozzle orifice diameter and EGR on the combustion (performance and emissions) characteristics of Mahua oil biodiesel blend. The specifications of the engine used is shown in Table 5. The engine was coupled to an eddy current dynamometer for loading the engine. For EGR, appropriate plumbing was done. To maintain the re-circulated exhaust gases partially cool, a water cooler was used while no insulation was considered on the pipeline to allow the escape of the heat. A control valve was installed to regulate the EGR percentage. An EGR mixture chamber was also provided to mix the exhaust gases with fresh air. The flow rate of the intake fresh air was monitored by an orifice meter. A schematic presentation of the engine setup coupled with the EGR system is shown in Figure 2. For EGR setup The EGR (%) was calculated according to the following equation (Eq. 1).

$$\text{EGR rate (\%)} = \frac{Q_{\text{without EGR}} - Q_{\text{EGR}}}{Q_{\text{without EGR}}} \times 100 \quad \text{Eq. 1}$$

Where, $Q_{\text{without EGR}}$ is the airflow rate without EGR, i.e., 26 kg/h and Q_{EGR} is the EGR flow rates investigated, i.e., 2.6 kg/h, 5.2 kg/h, and 7.8 kg/h.

An AVL gas analyzer was used to measure CO, NO_x, and HC. The exhaust gas smoke opacity was measured by an AVL smoke opacity meter.

2.4. Measuring devices; ranges, accuracies, and percentage uncertainties

The ranges and accuracies of the measuring devices used in the present investigation are shown in Table 6. While the percentage uncertainties of

Fig.2. Schematic diagram of an experimental setup.

various instruments and calculated parameters are tabulated in [Tables 7](#) and [8](#), respectively.

Table 5.
Specifications of the diesel engine used.

Name of the description	Details/value
Make of mode	TV1-KIRLOSKAR
Engine type	Four stroke, water cooled, single cylinder, DI diesel engine
Loading device	Eddy current dynamometer
No. of cylinder	One
Rated power (kW)	3.5
Constant speed (rpm)	1500
Swept volume (cc)	661
Stroke length (mm)	110
Cylinder bore (mm)	87.5
Compression ratio	17.5:1
Connecting rod length (mm)	234
Injection timing (°CA. bTDC)	23
Piston bowl	Hemispherical
Nozzle type	Multi-hole
Nozzle opening pressure (bar)	210
Number of nozzle hole	3
Modified nozzle spray hole diameter	0.28 mm (base) and 0.20 mm (modified)

Table 6.
Accuracies and ranges of the measuring devices used in this study.

Quantity	Range	Accuracy
AVL gas analyzer	NO _x : 0-5000ppm CO: 0-10% by vol. HC: 0-20000 ppm	± 50 ppm ± 0.03% ± 10 ppm
AVL smoke meter	0-100%	± 0.2%
Pressure Sensor		
Name: Dynamic pr. Transducer with built-in amplifier Make: PCB Piezotronics, Model: M111A22	(0-110 bars)	± 0.05 bar
Fuel flow sensor	0-5 psi	± 0.1 psi
Crank angle encoder	-	± 1°
Speed measuring	0-5000 rpm	± 10 rpm
Air flow sensor	0-3.500 mm of H ₂ O	± 1 mm of H ₂ O
Alternator	0-20 A, 0-450 V	± 0.55 A, ± 1 V
Thermocouples	0-1000°C	± 1°C

Table 7.
Uncertainties of the instruments used in this study.

Instruments	Percentage uncertainties
Pressure pick up	± 1.0
Crank angle encoder	± 0.2
Exhaust gas analyzer	
NO _x	± 0.2
CO	± 0.2
HC	± 0.2
Smoke intensity	± 1.0
Time	± 0.2
Burette for fuel measurement	± 1.5
Load indicator	± 0.5
Speed	± 0.2
Temperature	± 0.2

Table 8.
Uncertainties of the calculate parameters.

Parameter	Percentage uncertainties
Brake power	± 0.5
Brake specific fuel consumption	± 1.5
Brake thermal efficiency	± 1.0

2.5. Experimental testing procedure

As mentioned earlier (see [Section 2.2](#)), the present work was aimed at overcoming the shortcoming observed in our previous investigation using Mahua oil biodiesel blend, i.e., increased NO_x emissions in response to reduction in orifice NHD ([Vijay Kumar et al., 2018b](#)). More specifically, the two different fuels, i.e., neat diesel and B20 (20% v of Mahua oil biodiesel + 80% v of diesel) were used. Moreover, the base nozzle hole orifice diameter ($\phi = 0.280$ mm) and modified nozzle hole orifice diameter ($\phi = 0.20$ mm) were taken into account. Finally, the effect of EGR with three different rates (i.e., 10%, 20%, and 30%) was investigated. Baseline data were obtained by operating the engine at different loads with diesel fuel and base NHD and the experimental data were analyzed and compared with the baseline data.

3. Results and Discussion

3.1. Engine performance analysis

3.1.1. Brake specific fuel consumption and brake thermal efficiency

The variations in BSFC and BTE vs. full load BP for different combinations of nozzle orifice diameter, fuel type, and EGR rate are shown in [Figure 3](#). As can be seen, there was a negative correlation between BSFC and BP. It should be noted that BSFC trend generally depends on density, viscosity, calorific value, and chemical composition of a given fuel. As revealed in our previous report, the smaller orifice NHD, i.e., 0.20 mm, led to significantly less BSFC with both diesel and B20 because of the higher mixing rate achieved ([Vijay Kumar et al., 2018b](#)). In the present study, BSFC was reduced by implementing the EGR rate of 10% for both B20 and diesel fuel probably due to the returning of HC and that the partially-cooled EGR acted as a pre-heater of the intake mixture. Further increments of EGR rate, i.e., 20% and 30%, resulted in increases in BSFC at both lower and higher loads ([Fig. 3](#)) due to the lack of sufficient O₂ in the combustion chamber leading to incomplete combustion.

Fig.3. Variations in BSFC and BTE vs. full load BP for different combinations of nozzle orifice diameter, fuel type, and EGR rate.

There was a positive correlation between BTE and BP. When combusting neat diesel fuel, BTE was slightly increased by using the 0.20

mm nozzle hole orifice diameter with. While in the case of B20 and the modified orifice diameter, the increases observed in BTE in response to increasing BP were more pronounced. This could be ascribed to the presence of O₂ in biodiesel enhancing the combustion process and heat release. On the other hand, the small orifice NHD of 0.20 mm improved fuel vaporization and atomization. Using the modified nozzle orifice diameter and the partially-cooled EGR of 10%, BTE was slightly increased for both B20 and diesel fuel. This could be explained by the re-burning of HC in the combustion chamber with EGR. At high loads, BTE is generally decreased due to introduction of a rich fuel mixture generating higher levels of CO₂ and soot which could in turn lead to incomplete combustion. In line with that and as can also be seen in **Figure 3**, at higher loads and by using higher EGR rates of 20% and 30%, the re-burning of HC was much significant. Moreover, through the application high EGR rates, the in-cylinder temperature would be reduced and late HRR would occur leading to reduced peak pressure at different loads and consequently decreased BTE.

3.2. Combustion parameters analysis

3.2.1. In-cylinder pressure

The variations recorded in in-cylinder pressure against crank angle at full load condition for different combinations of nozzle orifice diameter, fuel type, and EGR rate are shown in **Figure 4**. The application of biodiesel blend and diesel fuel with smaller orifice diameter reduced the ID period because of the lower heat capacity as well as the increased O₂ content and cetane number. The peak pressure was decreased with the application of EGR rates. It should be noted that EGR is mainly composed of CO₂, soot, and H₂O resulting in reduced O₂ concentration in the combustion chamber. The EGR function and the associated dilution and thermal effects led to slower chemical reactions and consequently, delayed start of combustion (SOC) and lengthier ID period. The latter intensified the premixed combustion phase.

Fig.4. Variations in in-cylinder pressure against crank angle at full load for different combinations of nozzle orifice diameter, fuel type, and EGR rate.

3.2.2. Maximum in-cylinder pressure

The variations of maximum pressure at different percentages of full load BP for different combinations of nozzle orifice diameter, fuel type, and EGR rate are shown in **Figure 5**. The usage of biodiesel blend and diesel fuel with smaller orifice diameter reduced the ID period and led to increases in the pressure in the combustion chamber. As can be observed as BP was increased, the peak pressure increased as well. Comparing diesel and biodiesel blend at different EGR rates with the modified orifice diameter, it could be concluded that the application of EGR with B20 seemed to be more promising (**Fig. 5**) probably due to the O₂ concentration of the biodiesel-containing blend (Lai et al., 2011).

3.2.3. In-cylinder gas temperature

The variations in the in-cylinder gas temperature with respect to different percentages of full load BP for different combinations of nozzle orifice

Fig.5. Variations of maximum pressure at different percentages of full load BP for different combinations of nozzle orifice diameter, fuel type, and EGR rate.

diameter, fuel type, and EGR rate are shown in **Figure 6**. The in-cylinder gas temperature trend indicated that as the BP was increased, the gas temperature rose as well. Furthermore, the temperature was increased by reducing the orifice diameter using B20. This was ascribed to both the oxygen content of biodiesel (Lai et al., 2011) and the more efficient spraying of the fuel leading to more favorable atomization of the fuel particles and consequently more complete combustion process. When the diesel engine was operated with partially-cooled EGR, the temperature was reduced under all operating conditions. More specifically, there was a negative correlation between the in-cylinder gas temperature and the EGR rates. This could be explained by the decreasing O₂ availability and increasing specific heat of intake mixture in response to increasing EGR rates.

Fig.6. Variations in the in-cylinder gas temperature with respect to different percentages of full load BP for different combinations of nozzle orifice diameter, fuel type, and EGR rate.

3.2.4. Heat release rate

The variations in HRR against crank angle at full load condition for different combinations of nozzle orifice diameter, fuel type, and EGR rate are shown in **Figure 7**. HRR is mainly dependent on ID, heating value of fuel, and air-fuel mixing. In fact, HRR is used to identify the differences in the combustion rates of fuels, the fraction of fuel burnt in the premixed process, and the SOC. The HRR for B20 with 0.20 mm nozzle orifice diameter was found to be lower with the early SOC (**Fig. 7**).

As the EGR rate was increased for diesel and B20, the HRR was increased as well due to the late SOC which was caused by the recirculation of CO₂, soot, and H₂O. Overall, the EGR rate of 10% with B20 seemed to be more promising than the other EGR rates (**Fig. 7**).

Fig.7. Variations in HRR against crank angle at full load condition for different combinations of nozzle orifice diameter, fuel type, and EGR rate.

3.3. Engine emissions analysis

3.3.1. Carbon monoxide

The variations in CO emission at different percentages of full load BP for different combinations of nozzle orifice diameter, fuel type, and EGR rate are shown in **Figure 8**. CO is mainly formed due to incomplete combustion. This takes place when there is not enough O_2 present to react with fuel. By using the modified 0.20 mm nozzle orifice diameter with B20, CO emissions were reduced due to the better atomization of the fuel. Through the application of the partially-cooled EGR, the CO emissions were increased. More specifically, these increments in CO emissions were proportional with increasing EGR rates. The reason behind increased CO emissions was the low in-cylinder temperature and reduced peak pressure mainly caused by the recirculation of high amounts of unburnt soot, CO_2 , H_2O , as well as O_2 deficiency (Duraisamy et al., 2011).

Fig.8. variations in CO emission at different percentages of full load BP for different combinations of nozzle orifice diameter, fuel type, and EGR rate.

3.3.2. Hydrocarbon

The variations of unburned HC at different percentages of full load BP for different combinations of nozzle orifice diameter, fuel type, and EGR rate are shown in **Figure 9**. HC emissions originate from the presence of too many fuel particles left unburned in the combustion chamber due to incomplete combustion. It also appears in the inner layers during the diffusion flame where there is more fuel than air. As presented, HC emissions were substantially reduced by using the modified orifice diameter with both diesel and B20 fuel (**Fig. 9**). This was mainly ascribed to the more atomization of the fuel and proper air-fuel mixing in the combustion chamber. When EGR was used in combination with the modified orifice diameter and both B20 and diesel, increases in HC were recorded. At high loads and by using the EGR rate of 30%, HC emissions were drastically increased due to the reductions in in-cylinder temperature and pressure reduction. This was because of higher deficiency of O_2 leading the rich fuel mixture inside the combustion chamber

(Fontana and Galloni, 2010). In another word, such heterogeneous mixtures do not combust entirely and result in increased HC emissions at higher loads.

Fig.9. Variations of unburned HC at different percentages of full load BP for different combinations of nozzle orifice diameter, fuel type, and EGR rate.

3.3.3. Oxides of nitrogen

The variations of NO_x at different percentages of full load BP for different combinations of nozzle orifice diameter, fuel type, and EGR rate are shown in **Figure 10**. NO_x is generally formed when N_2 and O_2 react at high temperatures in the combustion process. The NO_x emissions measured for the modified orifice diameter stood higher. Using the biodiesel blend, NO_x must have been formed mainly in the premixed combustion and in the outer layers of the diffusion flame, where the temperature is high and there is a lot of O_2 presents (i.e., the O_2 contained in the B20). As shown in **Figure 10**, the application of the EGR substantially reduced the NO_x emissions. This was in line with the findings of the previous studies indicating that increasing EGR rates led to reduced NO_x formation (Sasaki et al., 1998; Mani et al., 2010). These results could be ascribed to the effect of EGE in decreasing O_2 concentration and flame temperature in the combustible mixture. This was also in line with the results obtained on in-cylinder temperature (**Figure 10**) implying reduced temperatures in response to increasing EGR rates.

Fig.10. Variations of NO_x at different percentages of full load BP for different combinations of nozzle orifice diameter, fuel type, and EGR rate.

3.3.4. Smoke opacity

The variations in smoke opacity at different percentages of full load BP for different combinations of nozzle orifice diameter, fuel type, and EGR rate are shown in **Figure 11**. Smoke opacity is measured to quantify the amount of particulate matter (PM) present in the exhaust gas. The modified orifice diameter reduced smoke opacity when combusting both diesel and B20. As the flow rate of EGR into the combustion chamber was increased, smoke opacity also increased. Comparing diesel and B20 at different EGR

rates, the latter led to more favorable results on smoke opacity because of the O_2 concentration present in biodiesel (Fig. 11). In another words, EGR reduced the availability of O_2 for the combustion of fuel, which in turn resulted in relatively incomplete combustion and increased formation of PM. The lower in-cylinder temperatures in response to the increasing EGR rates must have also contributed to the increases observed in smoke opacity (Rajan and Senthilkumar, 2009).

Fig.11. Variations in smoke opacity at different percentages of full load BP for different combinations of nozzle orifice diameter, fuel type, and EGR rate.

4. Conclusions

Experiments were conducted with neat diesel and 20% blend of Mahua oil biodiesel with base and modified NHD while different EGR rates (i.e., 10%, 20%, and 30%) were also employed to overcome the challenges faced regarding NO_x emissions. Combustion characteristics of different combinations of nozzle orifice diameter, fuel type, and EGR rate were recorded and the obtained data were compared with baseline data on neat diesel. Accordingly, the following main conclusions could be drawn:

- The smaller orifice NHD of 0.20 mm was substantially beneficial in improving the engine performance parameters, i.e., BTE, BSFC, P-0, and HRR as well as in reducing the emissions associated with both diesel and B20. However, the modification implemented led to increased NO_x which was a major drawback. These results were mainly attributed to the more efficient atomization and proper mixing of air-fuel mixtures in response to smaller orifice NHD.
- Partially-cooled EGR rate of 10% was found promising for both B20 and diesel when the proposed engine modification (i.e., smaller orifice NHD) was carried out.
- By increasing the EGR, NO_x emissions were drastically decreased at all the applied load conditions. This could be explained by the reduced O_2 concentration and reduced flame temperatures in the combustible mixture as a result of EGR implementation.
- Beyond the EGR rate of 10%, the performance, combustion, and emissions characteristics deteriorated mainly due to the recirculation of high amounts of unburnt soot, CO_2 , H_2O , as well as of O_2 deficiency.
- The application of high EGR rates led to increased soot formation by decreasing the availability of O_2 for fuel combustion and the consequent relatively incomplete combustion.

Overall and based on the findings of the present study, engine modification, i.e., shifting from the base orifice NHD of 0.28 mm to the modified value of 0.20 mm in the presence of partially-cooled EGR rate of 10% could be recommended as efficient combustion conditions for 20% blend of Mahua oil biodiesel and diesel.

Acknowledgements

The authors are very grateful to the Founding Chairman of the Malla Reddy Engineering College (Dhulapally, Secunderabad) and the Director of the National Institute of Technology Warangal for their support in the conducting of the present study.

References

- [1] Achten, W.M.J., Verchot, L., Franken, Y.J., Mathijs, E., Singh, V.P., Aerts, R., Muys, B., 2008. *Jatropha* bio-diesel production and use. *Biomass Bioenergy*. 32(12), 1063-1084.
- [2] Agarwal, A.K., Dhar, A., 2013. Experimental investigations of performance, emission and combustion characteristics of Karanja oil blends fuelled DI engine. *Renew. Energy*. 52, 283-291.
- [3] Atabani, A.E., Silitonga, A.S., Ong, H.C., Mahlia, T.M.I., Masjuki, H.H., Badruddin, I.A., Fayaz, H., 2013. Non-edible vegetable oils: a critical evaluation of oil extraction, fatty acid compositions, biodiesel production, characteristics, engine performance and emissions production. *Renew. Sust. Energy Rev.* 18, 211-245.
- [4] Azam, M.M., Waris, A., Nahar, N.M., 2005. Prospects and potential of fatty acid methyl esters of some non-traditional seed oils for use as biodiesel in India. *Biomass Bioenergy*. 29(4), 293-302.
- [5] Bai, Y.L., Wang, Z., Wang, J.X., 2010. Part load characteristics of direct injection spark ignition engine using exhaust gas trap. *Appl. Energy*. 87(8), 2640-2646.
- [6] Can, Ö., Öztürk, E., Solmaz, H., Aksoy, F., Çınar, C., Yücesu, H.S., 2016. Combined effects of soybean biodiesel fuel addition and EGR application on the combustion and exhaust emissions in a diesel engine. *Appl. Therm. Eng.* 95, 115-124.
- [7] Channapattana, S.V., Pawar, A.A., Kamble, P.G., 2015. Effect of injection pressure on the performance and emission characteristics of VCR engine using Honne biodiesel as a fuel. *Mater. Today Proc.* 2(4-5), 1316-1325.
- [8] Chauhan, B.S., Kumar, N., Cho, H.M., 2012. A study on the performance and emission of a diesel engine fueled with *Jatropha* biodiesel oil and its blends. *Energy*. 37(1), 616-622.
- [9] Chauhan, B.S., Kumar, N., Cho, H.M., Lim, H.C., 2013. A study on the performance and emission of a diesel engine fueled with Karanja biodiesel and its blends. *Energy*. 56, 1-7.
- [10] Dubey, P., Gupta, R., 2018. Influences of dual bio-fuel (*Jatropha* biodiesel and turpentine oil) on single cylinder variable compression ratio diesel engine. *Renew. Energy*. 115, 1294-1302.
- [11] Duraisamy, M.K., Balusamy, T., Senthilkumar, T., 2011. Reduction of NO_x emission in *Jatropha* seed oil fueled CI engine. *ARPN J. Eng. Appl. Sci.* 6(5), 34-39.
- [12] Fontana, G., Galloni, E., 2010. Experimental analysis of a spark-ignition engine using exhaust gas recycle at WOT operation. *Appl. Energy*. 87(7), 2187-2193.
- [13] Ganapathy, T., Gakkhar, R.P., Murugesan, K., 2011. Influence of injection timing on performance, combustion and emission characteristics of *Jatropha* biodiesel engine. *Appl. Energy*. 88(12), 4376-4386.
- [14] Gnanasekaran, S., Saravanan, N., Ilankumaran, M., 2016. Influence of injection timing on performance, emission and combustion characteristics of a DI diesel engine running on fish oil biodiesel. *Energy*. 116, 1218-1229.
- [15] Godiganur, S., Murthy, C.S., Reddy, R.P., 2009. 6BTA 5.9 G2-1 Cummins engine performance and emission tests using methyl ester mahua (*Madhuca indica*) oil/diesel blends. *Renew. Energy*. 34(10), 2172-2177.
- [16] Gui, M.M., Lee, K.T., Bhatia, S., 2008. Feasibility of edible oil vs. non-edible oil vs. waste edible oil as biodiesel feedstock. *Energy*. 33(11), 1646-1653.
- [17] Gumus, M., Sayin, C., Canakci, M., 2012. The impact of fuel injection pressure on the exhaust emissions of a direct injection diesel engine fueled with biodiesel-diesel fuel blends. *Fuel*. 95, 486-494.
- [18] Herbinet, O., Pitz, W.J., Westbrook, C.K., 2008. Westbrook. Detailed chemical kinetic oxidation mechanism for a biodiesel surrogate. *Combust. Flame*. 154(3), 507-528.
- [19] Hussain, J., Palaniradja, K., Alagumurthi, N., Manimaran, R., 2012. Petracted: effects of exhaust gas recirculation (EGR) on performance and emission characteristics of a three cylinder direct injection compression ignition engine. *Alexandria Eng. J.* 51(4), 241-247.
- [20] Hussain, J., Palaniradja, K., Alagumurthi, N., Manimaran, R., 2012. Retracted: effect of exhaust gas recirculation (EGR) on

- performance and emission characteristics of a three cylinder direct injection compression ignition engine. *Alexandria Eng. J.* 51(4), 241-247.
- [21] Jena, P.C., Raheman, H., Kumar, G.P., Machavaram, R., 2010. Biodiesel production from mixture of mahua and simarouba oils with high free fatty acids. *Biomass Bioenergy*. 34(8), 1108-1116.
- [22] Jindal, S., Nandwana, B.P., Rathore, N.S., Vashistha, V., 2010. Experimental investigation of the effect of compression ratio and injection pressure in a direct injection diesel engine running on *Jatropha methyl ester*. *Appl. Therm. Eng.* 30(5), 442-448.
- [23] Karmee, S.K., Chadha, A., 2005. Preparation of biodiesel from crude oil of *Pongamia pinnata*. *Bioresour. Technol.* 96(13), 1425-1429.
- [24] Koh, M.Y., Ghazi, T.I.M., 2011. A review of biodiesel production from *Jatropha curcas* L. oil. *Renew. Sust. Energy Rev.* 15(5), 2240-2251.
- [25] Koutroubas, S.D., Papakosta, D.K., Doitsinis, A., 1999. Adaptation and yielding ability of castor plant (*Ricinus communis* L.) genotypes in a Mediterranean climate. *Eur. J. Agron.* 11(3-4), 227-237.
- [26] Kumar, A., Sharma, S., 2011. Potential non-edible oil resources as biodiesel feedstock: an Indian perspective. *Renew. Sust. Energy Rev.* 15(4), 1791-1800.
- [27] Kusaka, J., Okamoto, T., Daisho, Y., Kihara, R., Saito, T., 2000. Combustion and exhaust gas emission characteristics of a diesel engine dual-fueled with natural gas. *JSAE Rev.* 21(4), 489-496.
- [28] Lai, J.Y., Lin, K.C., Violi, A., 2011. Biodiesel combustion: advances in chemical kinetic modeling. *Prog. Energy Combust. Sci.* 37(1), 1-14.
- [29] Liaquat, A.M., Masjuki, H.H., Kalam, M.A., Varman, M., Hazrat, M.A., Shahabuddin, M., Mofijur, M., 2012. Application of blend fuels in a diesel engine. *Energy Procedia*. 14, 1124-1133.
- [30] Mani, M., Nagarajan, G., Sampath, S., 2010. An experimental investigation on a DI diesel engine using waste plastic oil with exhaust gas recirculation. *Fuel*. 89(8), 1826-1832.
- [31] Mofijur, M., Masjuki, H.H., Kalam, M.A., Atabani, A.E., 2013. Evaluation of biodiesel blending, engine performance and emissions characteristics of *Jatropha curcas* methyl ester: Malaysian perspective. *Energy*. 55, 879-887.
- [32] Mo, J., Tang, C., Li, J., Guan, L., Huang, Z., 2016. Experimental investigation on the effect of *n*-butanol blending on spray characteristics of soybean biodiesel in a common-rail fuel injection system. *Fuel*. 182, 391-401.
- [33] Nabi, M.N., Akhter, M.S., Shahadat, M.M.Z., 2006. Improvement of engine emissions with conventional diesel fuel and diesel-biodiesel blends. *Bioresour. Technol.* 97(3), 372-378.
- [34] Naik, M., Meher, L.C., Naik, S.N., Das, L.M., 2008. Production of biodiesel from high free fatty acid karanja (*Pongamia pinnata*) oil. *Biomass Bioenergy*. 32(4), 354-357.
- [35] No, S.Y., 2011. Inedible vegetable oils and their derivatives for alternative diesel fuels in CI engines: a review. *Renew. Sust. Energy Rev.* 15(1), 131-49.
- [36] Pinzi, S., Garcia, I.L., Lopez-Gimenez, F.J., Luque de Castro, M.D., Dorado, G., Dorado, M.P., 2009. The ideal vegetable oil-based biodiesel composition: a review of social, economical and technical implications. *Energy Fuels*. 23(5), 2325-2341.
- [37] Raheman, H., Ghadge, S.V., 2007. Performance of compression ignition engine with mahua (*Madhuca indica*) biodiesel. *Fuel*. 86(16), 2568-2573.
- [38] Raheman, H., Phadatare, A.G., 2004. Diesel engine emissions and performance from blends of karanja methyl ester and diesel. *Biomass Bioenergy*. 27(4), 393-397.
- [39] Rahman, S.A., Masjuki, H.H., Kalam, M.A., Abedin, M.J., Sanjid, A., Rahman, M.M., 2014. Assessing idling effects on a compression ignition engine fueled with *Jatropha* and *Palm* biodiesel blends. *Renew. Energy*. 68, 644-650.
- [40] Rahman, S.A., Masjuki, H.H., Kalam, M.A., Abedin, M.J., Sanjid, A., Imtenan, S., 2014. Effect of idling on fuel consumption and emissions of a diesel engine fueled by *Jatropha* biodiesel blends. *J. Cleaner Prod.* 69, 208-215.
- [41] Rajan, K., Senthilkumar, K.R., 2009. Effect of EGR on performance and emission characteristics of diesel engine with sunflower oil methyl ester. *Jordan J. Mech. Ind. Eng.* 3(4), 306-311.
- [42] Ramadan, M.F., Moersel, J.T., 2003. Phospholipid composition of niger (*Guizotia abyssinica cass.*) seedoil. *LWT-Food Sci. Technol.* 36(2), 273-276.
- [43] Ramadhas, A.S., Jayaraj, S., Muraleedharan, C., 2005a. Biodiesel production from high FFA rubber seed oil. *Fuel*. 84(4), 335-340.
- [44] Ramadhas, A.S., Jayaraj, S., Muraleedharan, C., 2005b. Characterization and effect of using rubber seed oil as fuel in the compression ignition engines. *Renew. Energy*. 30(5), 795-803.
- [45] Sahoo, P.K., Das, L.M., Babu, M.K.G., Naik, S.N., 2007. Biodiesel development from high acid value polanga seed oil and performance evaluation in a CI engine. *Fuel*. 86(3), 448-454.
- [46] Saka, S., 2005. Production of biodiesel: current and future technology. In *JSPS/VCO Core University program seminar, Universiti Sains Malaysia*. 62-102.
- [47] Sasaki, S., Sawada, D., Ueda, T., Sami, H., 1998. Effect of EGR on direct injection gasoline engine. *JSAE Rev.* 19(3), 223-228.
- [48] Sharma, V., Das, L., Pradhan, R.C., Naik, S.N., Bhatnagar, N., Kureel, R.S., 2011. Physical properties of tung seed: an industrial oil yielding crop. *Ind. Crops Prod.* 33(2), 440-444.
- [49] Shehata, M.S., Attia, A.M., Razeq, S.A., 2015. Corn and soybean biodiesel blends as alternative fuels for diesel engine at different injection pressures. *Fuel*. 161, 49-58.
- [50] Silitonga, A.S., Atabani, A.E., Mahlia, T.M.I., Masjuki, H.H., Badruddin, I.A., Mekhilef, S., 2011. A review on prospect of *Jatropha curcas* for biodiesel in Indonesia. *Renew. Sust. Energy Rev.* 15(8), 3733-3756.
- [51] Singh, S.P., Singh, D., 2010. Biodiesel production through the use of different sources and characterization of oils and their esters as the substitute of diesel: a review. *Renew. Sust. Energy Rev.* 14(1), 200-216.
- [52] Sivaramakrishnan, K., 2018. Investigation on performance and emission characteristics of a variable compression multi fuel engine fuelled with Karanja biodieseldiesel blend. *Egypt. J. Pet.* 27(2), 177-186.
- [53] Sureshkumar, K., Velraj, R., Ganesan, R., 2008. Performance and exhaust emission characteristics of a CI engine fueled with *Pongamia pinnata* methyl ester (PPME) and its blends with diesel. *Renew. Energy*. 33(10), 2294-2302.
- [54] Venkanna, B.K., Reddy, C.V., 2009. Biodiesel production and optimization from *Calophyllum inophyllum* linn oil (honne oil)-A three stage method. *Bioresour. Technol.* 100(21), 5122-5125.
- [55] Vijay Kumar, M., Veeresh Babu, A., Ravi Kumar, P., 2017a. Producing biodiesel from crude Mahua oil by two steps of transesterification process. *Aust. J. Mech. Eng.* 1-6.
- [56] Vijay Kumar, M., Veeresh Babu, A., Ravi Kumar, P., 2017b. Experimental investigation on Mahua methyl ester blended with diesel fuel in a compression ignition diesel engine. *Int. J. Ambient Energy*. 1-13.
- [57] Vijay Kumar, M., Veeresh Babu, A., Ravi Kumar, P., 2018a. The impacts on combustion, performance and emissions of biodiesel by using additives in direct injection diesel engine. *Alexandria Eng. J.* 57(1), 509-516.
- [58] Vijay Kumar, M., Veeresh Babu, A., Ravi Kumar, P., 2018b. Experimental investigation on the effects of diesel and Mahua biodiesel blended fuel in direct injection diesel engine modified by nozzle orifice diameters. *Renew. Energy*. 119, 388-399.
- [59] Vijayaraj, K., Sathiyagnanam, A.P., 2016. Experimental investigation of a diesel engine with methyl ester of mango seed oil and diesel blends. *Alexandria Eng. J.* 55(1), 215-221.